

# Sutherland Welles Ltd.®

*Sustainable, natural & earth-friendly Polymerized Tung Oil wood finishes.*



## Murdoch's Hard Sealer or Uralkyd 500 Floor Finish

When a more durable or glossy surface is desired Murdoch's Hard Sealer is the perfect solution on your porous stone. In addition to sealing the stone it also seals the grout. For maximum durability and / or a lower sheen use the Murdoch's Uralkyd 500 Floor Finish in Matte or Satin.

### Grout Release Instructions

#### step 1:

- Apply Hard Sealer
- Let cure 24 hours

#### step 2:

- Apply Hard Sealer
- Let cure 24 hours

#### step 2:

- Grout stone

Follow manufactures instructions for cleaning and curing time.

Then continue on to perfered top coat application to seal the grout and stone.

### Top Coat Instructions Medium Sheen

#### step 1:

- Apply Hard Sealer
- Let cure 24 hours

#### step 2:

- Apply Hard Sealer
- Let cure 24 hours

## Porous Stone

### Stone Preparation

All stone surfaces should be free of lint, dirt, grease, wax, oil. Clean the stone surface with 1 cup ammonia and 1 gallon water. Dry thoroughly.

### Applicator Options

**Brush:** Natural white china bristle brush (thin coats only)

### Cure Test

Lightly sand several inconspicuous areas. A fine, white powder indicates that you can safely apply another coat.

### Top Coat Instructions Matte or Satin Sheen

#### Uralkyd Matte

##### step 1:

- Apply Uralkyd Matte
- Let cure 24 hours

##### step 2:

- Apply Uralkyd Matte
- Let cure 24 hours

#### Uralkyd Satin

##### step 1:

- Apply Uralkyd Satin
- Let cure 24 hours

##### step 2:

- Apply Uralkyd Satin
- Let cure 24 hours