

**Material Safety Data Sheet**  
**Sutherland Welles Ltd.®**  
**P.O. Box 180**  
**North Hyde Park, VT 05665**

**SECTION 1 - PRODUCT IDENTIFICATION**

---

**MANUFACTURER:** SUTHERLAND WELLES LTD® **EMERGENCY PHONE #:** (800) 322-1245 **FAX:** (802) 635-2722

**MANUFACTURER ADDRESS:** P.O. BOX 180, 5575 ROUTE 100 NORTH, NORTH HYDE PARK,VT. 05665

**TRADE NAME:** MURDOCH'S TABLE TOP™SATIN

**CHEMICAL FAMILY:** POLYURETHANE/POLYMERIZED TUNG OIL

**FORMULA:** MURTTTS

**UN #- 1263**

**PACKING GROUP III**

**SECTION 2 - HAZARD IDENTIFICATION**

---

THIS MATERIAL IS CONSIDERED TO BE HAZARDOUS ACCORDING TO REGULATORY GUIDELINES (SEE (M)SDS SECTION 15).

**POTENTIAL PHYSICAL / CHEMICAL EFFECTS**

COMBUSTIBLE. MATERIAL CAN RELEASE VAPORS THAT READILY FORM FLAMMABLE MIXTURES. VAPOR ACCUMULATION COULD FLASH AND/OR EXPLODE IF IGNITED. MATERIAL CAN ACCUMULATE STATIC CHARGES WHICH MAY CAUSE AN IGNITION.

**POTENTIAL HEALTH EFFECTS**

REPEATED EXPOSURE MAY CAUSE SKIN DRYNESS OR CRACKING. IF SWALLOWED, MAY BE ASPIRATED AND CAUSE LUNG DAMAGE. MAY BE IRRITATING TO THE EYES, NOSE, THROAT, AND LUNGS.



GHS08 · SIGNAL WORD: WARNING

P210 KEEP AWAY FROM HEAT/SPARKS/OPEN FLAMES/HOT SURFACES.

H320 CAUSES EYE IRRITATION

P264 WASH THOROUGHLY AFTER HANDLING.

P280 WEAR PROTECTIVE GEAR. PROTECTIVE GLOVES/PROTECTIVE CLOTHING/EYE PROTECTION/FACE PROTECTION.

P305+P351+P338 IF IN YES: RINSE CAUTIOUSLY WITH WATER FOR SEVERAL MINUTES.REMOVE CONTACT LENSES, IF PRESENT, AND CONTINUE RINSING.

**HMIS RANKING:**

**HEALTH:.....2**

**FIRE: .....2**

**REACTIVITY:. 0**

**HMIS CODE:**

**0= LEAST**

**1= SLIGHT**

**2= MODERATE**

**3= HIGH**

**4= EXTREME**

**NOTE:** THIS MATERIAL SHOULD NOT BE USED FOR ANY OTHER PURPOSE THAN THE INTENDED USE IN SECTION 1 WITHOUT EXPERT ADVICE. HEALTH STUDIES HAVE SHOWN THAT CHEMICAL EXPOSURE MAY CAUSE POTENTIAL HUMAN HEALTH RISKS WHICH MAY VARY FROM PERSON TO PERSON.

**SECTION 3 – COMPOSITION INFORMATION**

---

<b>NAME:</b>	<b>% BY WGT:</b>	<b>CAS # :</b>	<b>TLV:</b>
DICITRUSOL™	20%	5989-27-5	UNDETERMINED
DISTILLATES, PETROLEUM	20%	64742-47-8	100PPM

#### **SECTION 4 – FIRST AID MEASURES**

---

**EYE CONTACT:**

REMOVE CONTACT LENSES. FLUSH WITH WATER FOR 15 MINUTES. SEE DOCTOR.

**INHALATION:**

MOVE TO FRESH AIR. SEE DOCTOR.

**SKIN CONTACT:**

WASH WITH SOAP AND WATER. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

**INGESTION:**

CALL A DOCTOR IMMEDIATELY. DO NOT INDUCE VOMITING.

**\*NOTE TO PHYSICIAN: PERFORM GASTRIC LAVAGE IN ACCORDANCE WITH PROCEDURE FOR INGESTION OF PETROLEUM PRODUCTS.\***

#### **SECTION 5 - FIRE FIGHTING MEASURES**

---

**FLASH POINT:** 113°F >400 ASTM-D-56

**EXTINGUISHING MEDIA:** CARBON DIOXIDE, FOAM, OR DRY CHEMICAL

**SPECIAL FIRE FIGHTING PROCEDURE:** COOL CLOSED CONTAINERS EXPOSED TO HEAT BY WATER.  
USUAL PRECAUTIONS FOR COMBUSTIBLE LIQUIDS.

#### **SECTION 6 – ACCIDENTAL RELEASE (SPILL) MEASURES**

---

**STEPS TO BE TAKEN IN CASE OF SPILL OR LEAKAGE:**

SMALL SPILLS - WIPE UP WITH RAGS.

LARGE SPILLS - USE NON-FLAMMABLE ABSORBENT. KEEP AWAY FROM FLAME OR SPARK.

**WASTE DISPOSAL METHOD:** LANDFILL OR INCINERATE IN ACCORDANCE WITH ALL LOCAL STATE AND FEDERAL REGULATIONS.

**EYE CONTACT:** MODERATELY IRRITATING TO THE EYES. FLUSH WITH WATER.

**SKIN CONTACT:** PROLONGED OR REPEATED CONTACT WITH SKIN CAN BE MILDLY IRRITATING AND RESULT IN DRYING AND IRRITATION, WASH WITH SOAP AND WATER.

**INHALATION:** HIGH VAPOR CONCENTRATIONS MAY IRRITATE RESPIRATORY AIRWAYS, NOSE AND THROAT.

**INGESTION:** DO NOT INDUCE VOMITING! SEEK MEDICAL ATTENTION.

**NOTE TO PHYSICIAN:** PERFORM GASTRIC LAVAGE IN ACCORDANCE WITH PROCEDURE FOR INGESTION OF PETROLEUM PRODUCTS.

#### **SECTION 7 - HANDLING AND STORAGE**

---

**STABILITY:** STABLE UNDER MOST CONDITIONS.

**CONDITIONS TO AVOID:** EXCESSIVE HEAT

**INCOMPATIBILITY (MATERIALS TO AVOID):** STRONG OXIDIZING AGENTS AND ACIDS

**HAZARDOUS DECOMPOSITION PRODUCTS:** CARBON MONOXIDE IS A PRODUCT OF INCOMPLETE COMBUSTION.

**HAZARDOUS POLYMERIZATION:** NONE.

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING :** TO BE HANDLED WITH GOOD INDUSTRIAL PRACTICE.

**OTHER PRECAUTIONS:** NONE.

**SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION**



**RESPIRATORY PROTECTION:** USE AIR SUPPLIED MASKS IN CLOSED AND CONFINED SPACES.  
**VENTILATION:**  
**LOCAL EXHAUST:** YES, IN ENCLOSED AREAS.  
**MECHANICAL:** IN ENCLOSED AREAS  
**SPECIAL:**  
**OTHER:**



**PROTECTIVE RUBBER OR PLASTIC GLOVES:** YES



**EYE PROTECTION SPLASH PROOF GLASSES OR GOGGLES:** YES

**OTHER PROTECTIVE EQUIPMENT AS REQUIRED BY YOUR COMPANY:** NONE.

**SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES**

**BOILING POINT:** 315°F

**ODOR:** MILD CITRUS

**APPEARANCE:** CLEAR, LIGHT AMBER COLOR

**SPECIFIC GRAVITY:** .88

**PERCENT VOLATILE:** 60-65% BY WEIGHT

**VOC:** VARNISH: 450GM/L OR LESS

**SECTION 10 – STABILITY AND REACTIVITY**

**STABILITY:** STABLE UNDER MOST CONDITIONS.

**CONDITIONS TO AVOID:** EXCESSIVE HEAT

**INCOMPATIBILITY (MATERIALS TO AVOID):** STRONG OXIDIZING AGENTS AND ACIDS

**SECTION 11 - TOXICOLOGICAL INFORMATION**

**ACUTE TOXICITY**

<b>ROUTE OF EXPOSURE</b>	<b>CONCLUSION / REMARKS</b>
<b>INHALATION:</b>	HIGH VAPOR CONCENTRATIONS MAY IRRITATE RESPIRATORY AIRWAYS, NOSE AND THROAT
<b>TOXICITY</b>	MINIMALLY TOXIC, BASED ON TEST DATA FOR STRUCTURALLY SIMILAR MATERIALS
<b>IRRITATION</b>	NEGLIGIBLE HAZARD AT AMBIENT/NORMAL HANDLING TEMPERATURES.
-----	-----
<b>INGESTION:</b>	
<b>TOXICITY- LD50&gt;5000 mg/kg</b>	MINIMALLY TOXIC. BASED ON TEST DATA FOR STRUCTURALLY SIMILAR MATERIALS
-----	-----
<b>SKIN:</b>	
<b>TOXICITY – LD50&gt;5000 mg/kg</b>	MINIMALLY TOXIC. BASED ON TEST DATA FOR STRUCTURALLY SIMILAR MATERIALS
<b>IRRITATION</b>	MILDLY IRRITATING TO SKIN WITH PROLONGED EXPOSURE
-----	-----
<b>EYE:</b>	
<b>IRRITATION</b>	MAY CAUSE MILD, SHORT-LASTING DISCOMFORT TO EYES

## SECTION 12 – ECOLOGICAL INFORMATION

---

THE INFORMATION GIVEN IS BASED ON DATA AVAILABLE FOR THE MATERIAL, THE COMPONENTS OF THE MATERIAL, AND SIMILAR MATERIALS.

### ECOTOXICITY

MATERIAL – PRODUCT IS A MARINE POLLUTANT AND TOXIC TO AQUATIC ORGANISMS

### PERSISTENCE AND DEGRADABILITY

#### BIODEGRADATION:

MATERIAL – 92.7% IN 21 DAYS PER METHOD CEC L33T82

#### HYDROLYSIS:

MATERIAL – TRANSFORMATION DUE TO HYDROLYSIS NOT EXPECTED TO BE SIGNIFICANT

#### PHOTOLYSIS:

MATERIAL – TRANSFORMATION DUE TO PHOTOLYSIS NOT EXPECTED TO BE SIGNIFICANT

#### ATMOSPHERIC OXIDATION:

MATERIAL – EXPECTED TO DEGRADE RAPIDLY IN AIR

## SECTION 13 – DISPOSAL CONSIDERATIONS

---

DISPOSAL RECOMMENDATIONS BASED ON MATERIAL AS SUPPLIED. DISPOSAL MUST BE IN ACCORDANCE WITH CURRENT APPLICABLE LAWS AND REGULATIONS, AND MATERIAL CHARACTERISTICS AT TIME OF DISPOSAL.

### DISPOSAL RECOMMENDATIONS

SUPERVISED INCINERATION AT VERY HIGH TEMPERATURES TO PREVENT FORMATION OF UNDESIRABLE COMBUSTION PRODUCTS.

LANDFILL IN ACCORDANCE WITH ALL LOCAL STATE AND FEDERAL REGULATIONS.

### REGULATORY DISPOSAL INFORMATION

RCRA INFORMATION: DISPOSAL OF UNUSED PRODUCT MAY BE SUBJECT TO RCRA REGULATIONS (40 CFR 261). DISPOSAL OF THE UNUSED PRODUCT MAY ALSO BE REGULATED DUE TO IGNITABILITY, CORROSIVITY, REACTIVITY OR TOXICITY AS DETERMINED BY THE TOXICITY CHARACTERISTIC LEACHING PROCEDURE (TCLP). POTENTIAL RCRA CHARACTERISTICS: **IGNITABILITY**

### EMPTY CONTAINERS

EMPTY CONTAINERS SHOULD BE TAKEN FOR RECYCLING, RECOVERY, OR DISPOSAL THROUGH SUITABLY QUALIFIED OR LICENSED CONTRACTORS AND IN ACCORDANCE WITH GOVERNMENTAL REGULATIONS.

## SECTION 14 – TRANSPORT INFORMATION

---

### LAND (DOT)

**PROPER SHIPPING NAME:** MURDOCH'S TABLE TOP™ SATIN WITH TERPENE HYDROCARBONS N.O.S.

**HAZARD CLASS & DIVISION:** COMBUSTIBLE LIQUID

**ID NUMBER:** 1263

**PACKING GROUP:** III

**ERG NUMBER:** 128

**LABEL(S):** NONE

**TRANSPORT DOCUMENT NAME:** UN1263 MURDOCH'S TABLE TOP™ SATIN WITH TERPENE HYDROCARBONS N.O.S., COMBUSTIBLE LIQUID, PG III

FOOTNOTE: THE FLASHPOINT OF THIS MATERIAL IS GREATER THAN 100F. REGULATORY CLASSIFICATION OF THIS MATERIAL VARIES. DOT: FLAMMABLE LIQUID OR COMBUSTIBLE LIQUID. OSHA: COMBUSTIBLE LIQUID. IATA/IMO: FLAMMABLE LIQUID. THIS MATERIAL IS NOT REGULATED UNDER 49 CFR IN A CONTAINER OF 119 GALLON CAPACITY OR LESS WHEN TRANSPORTED SOLELY BY LAND, AS LONG AS THE MATERIAL IS NOT A HAZARDOUS WASTE, A MARINE POLLUTANT, OR SPECIFICALLY LISTED AS A HAZARDOUS SUBSTANCE.

### LAND (TDG)

**PROPER SHIPPING NAME:** MURDOCH'S TABLE TOP™ SATIN WITH TERPENE HYDROCARBONS N.O.S.

**HAZARD CLASS & DIVISION:** 3

**ID NUMBER:** 1263

**PACKING GROUP:** III

FOOTNOTE: IN CONTAINERS OF 454 LITRES OR LESS THIS MATERIAL IS EXEMPT FROM TDG REGULATIONS.

**SEA (IMDG)**

**PROPER SHIPPING NAME:** MURDOCH'S TABLE TOP™ SATIN WITH TERPENE HYDROCARBONS N.O.S.  
**HAZARD CLASS & DIVISION:** COMBUSTIBLE LIQUID  
**EMS NUMBER:** F-E, S-E  
**UN NUMBER:** 1263  
**PACKING GROUP:** III  
**LABEL(S):** 3  
**TRANSPORT DOCUMENT NAME:** UN1263, MURDOCH'S TABLE TOP™SATIN WITH TERPENE HYDROCARBONS N.O.S., COMBUSTIBLE LIQUID, PG III, (40°C c.c.)

**AIR (IATA)**

**PROPER SHIPPING NAME:** MURDOCH'S TABLE TOP™ SATIN WITH TERPENE HYDROCARBONS, N.O.S.  
**HAZARD CLASS & DIVISION:** COMBUSTIBLE LIQUID  
**UN NUMBER:** 1263  
**PACKING GROUP:** III  
**LABEL(S) / MARK(S):** 3  
**TRANSPORT DOCUMENT NAME:** UN1263 MURDOCH'S TABLE TOP™SATIN WITH TERPENE HYDROCARBONS N.O.S., COMBUSTIBLE LIQUID, PG III

**SECTION 15 – REGULATORY INFORMATION**

**OSHA HAZARD COMMUNICATION STANDARD:** WHEN USED FOR ITS INTENDED PURPOSE, THIS MATERIAL IS CLASSIFIED AS HAZARDOUS IN ACCORDANCE WITH OSHA 29CFR 1910.1200

**NATIONAL CHEMICAL INVENTORY LISTING:** AICS, IECSC, DSL, EINECS, ENCS, KECI, PICCS, TSCA

**EPCRA:** THIS MATERIAL CONTAINS NO EXTREMELY HAZARDOUS SUBSTANCES.

**SARA (311/312) REPORTABLE HAZARD CATEGORIES:** FIRE

**SARA (313) TOXIC RELEASE INVENTORY:** THIS MATERIAL CONTAINS NO CHEMICALS SUBJECT TO THE SUPPLIER NOTIFICATION REQUIREMENTS OF THE SARA 313 TOXIC RELEASE PROGRAM.

**THE FOLLOWING INGREDIENTS ARE CITED ON THE LISTS BELOW:**

<u>CHEMICAL NAME</u>	<u>CAS NUMBER</u>	<u>LIST CITATIONS</u>
TERPENE HYDROCARBONS	5989-27-5	17, 18, 19

**-REGULATORY LISTS SEARCHED-**

1 = ACGIH ALL	6 = TSCA 5a2	11 = CA P65 REPRO	16 = MN RTK
2 = ACGIH A1	7 = TSCA 5e	12 = CA RTK	17 = NJ RTK
3 = ACGIH A2	8 = TSCA 6	13 = IL RTK	18 = PA RTK
4 = OSHA Z	9 = TSCA 12b	14 = LA RTK	19 = RI RTK
5 = TSCA 4	10 = CA P65 CARC	15 = MI 293	

**CODE KEY:** CARC=CARCINOGEN; REPRO=REPRODUCTIVE

**SECTION 16 – OTHER INFORMATION**

**THIS MATERIAL SAFETY DATA SHEET CONTAINS THE FOLLOWING REVISIONS:**

REVISION CHANGES:

THE FORMAT AND ORDER OF THIS (MSDS) SHEET HAS BEEN CHANGED TO BE COMPLIANT WITH THE HAZARD COMMUNICATION STANDARD (HCS) REQUIREMENTS STARTING JUNE 1, 2015. INCLUDED IN THE FORMAT AND ORDERING CHANGES TO THIS (MSDS) SHEET ARE:

**SECTION 12:** THIS SECTION'S ENTIRETY WAS ADDED TO MEET JUNE 1, 2015 STANDARD REQUIREMENTS

**SECTION 13:** THIS SECTION'S ENTIRETY WAS ADDED TO MEET JUNE 1, 2015 STANDARD REQUIREMENTS

**SECTION 14:** THIS SECTION'S ENTIRETY WAS ADDED TO MEET JUNE 1, 2015 STANDARD REQUIREMENTS

**SECTION 15:** THIS SECTION'S ENTIRETY WAS ADDED TO MEET JUNE 1, 2015 STANDARD REQUIREMENTS

**SECTION 2:** POTENTIAL PHYSICAL / CHEMICAL EFFECTS HAVE BEEN MODIFIED

**SECTION 2:** POTENTIAL HEALTH EFFECTS HAVE BEEN MODIFIED

**SECTION 4:** FORMATTING FOR THIS SECTION HAS BEEN MODIFIED

REVISED: 01/02/17