

Sutherland Welles Ltd.®

Sustainable, natural & earth-friendly Polymerized Tung Oil wood finishes.



Murdoch's Hard Sealer or Uralkyd 500 Floor Finish

When a more durable or glossy surface is desired Murdoch's Hard Sealer is the perfect solution on your porous stone. In addition to sealing the stone it also seals the grout. For maximum durability and / or a lower sheen use the Murdoch's Uralkyd 500 Floor Finish in Matte or Satin.

Grout Release Instructions *Hard Sealer*

step 1:

- Apply *Hard Sealer*
- Let cure 24 hours

step 2:

- Apply *Hard Sealer*
- Let cure 24 hours

step 2:

- Grout stone

Follow manufacturers instructions for cleaning and curing time.

Then continue on to perfered top coat application to seal the grout and stone.

Top Coat Instructions Medium Sheen

Hard Sealer ONLY

step 1:

- Apply *Hard Sealer*
- Don't Wipe
- Let cure 24 hours

- step 2:

- Apply *Hard Sealer*
- Don't Wipe
- Let cure 24 hours

Top Coat Instructions Matte or Satin Sheen

Uralkyd 500 Matte

step 1:

- Apply *Uralkyd 500 Matte*
- Don't Wipe
- Let cure 24 hours

- step 2:

- Apply *Uralkyd 500 Matte*
- Don't Wipe
- Let cure 24 hours

Uralkyd 500 Satin

step 1:

- Apply *Uralkyd 500 Satin*
- Don't Wipe
- Let cure 24 hours

- step 2:

- Apply *Uralkyd 500 Satin*
- Don't Wipe
- Let cure 24 hours

Porous Stone

Stone Preparation

All stone surfaces should be free of lint, dirt, grease, wax, oil. Clean the stone surface with 1 cup ammonia and 1 gallon water. Dry thoroughly.

Applicator Options

Brush: Natural white china bristle brush (thin coats only)

Cure Test

Lightly sand several inconspicuous areas. A fine, white powder indicates that you can safely apply another coat.

Gentle use after 24 hours. Resin fully cures through 7-14 days & full tung oil cure through after 30 days (+/- based on local humidity/elevation/temperature)