

SUTHERLAND WELLES LTD.®

AQUA GLAZE

Water Base Glazing
Compound

For use with water based paints • Fast dry
• Interior/exterior • Paintable in 30 minutes
• Water clean up • Clean air formula

- Face glaze wood and metal sash
- Paintable within 30 minutes
- Excellent for filling countersunk nailheads
- For use under all types of paints
- Clean up with water

Aqua-Glaze Glazing Compound

Description

Sutherland Welles' Aqua-Glaze is a water base compound used to face glaze wood and metal sash. It is also excellent for filling countersunk nailheads, crevices and cracks. Aqua-Glaze is specifically designed for use under all types of interior and exterior paints. Painters prefer it for its quick dry time. Cleanup with water is easy.

Application

Surfaces and air temperature should be above 40°F. Prime unpainted wood. Make sure that surfaces are clean, dry, frost free and free of sandpaper dust. All old flaking paint and dried putty should be thoroughly removed for proper adhesion. Countersink nails at least 3/16", fill and prime. Steel sash and other surfaces that rust must be primed with a rust preventing primer. Knead Aqua-Glaze in hands and roll to warm for smoother application. Apply to surface with putty knife or spread firmly with fingers. Aqua-Glaze can be painted in 30 minutes (with proper conditions) with water base or conventional oil based paints. Cleanup with water.

Typical Properties

Consistency: Knife grade mastic

Non-volatile: 85%

Binder: Acrylic Latex

Color: White

Weight per Gallon: 16 lbs

Surface Dry: 30 minutes

Prod Code:	Sizes:	Pkd:	UPC:	Ship Wt:
021016	½ Pint	12/case	0 82069 03016 7	16 lbs.
021004	Quart	6/case	0 82069 03004 4	30 lbs.
021001	Gallon	2/case	0 82069 03001 3	35 lbs.

Sutherland Welles Ltd 8 Robin St, Providence RI 02908 (401) 443-1884

Email: info@aqua-glaze.com

www.aqua-glaze.com