



Murdoch's Hard Sealer

Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)
Issue date: 9/8/2026 Version: 1.0

SECTION 1 Identification

1.1. Product identifier

Product form : Mixture
Trade name : Murdoch's Hard Sealer

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Use of the substance/mixture : Wood finishing
Restrictions on use : None known

1.4. Supplier's details

Sutherland Welles Ltd.®
8 Robin Street
Providence, RI 02908-5505
USA
T 1.800.322.1245
info@sutherlandwelles.com

1.5. Emergency phone number

Emergency number : For Hazardous Materials or Dangerous Goods Incident Spill, Leak, Fire, Exposure, or Accident
Call CHEMTREC Day or Night: 1-800-424-9300 (Toll Free, USA) / 703-527-3887 (Virginia, USA)
CCN 854332
Back-up Emergency Number: +1 703-741-5970 (Washington, DC)

SECTION 2 Hazard Identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquid, Category 3	H226	Flammable liquid and vapor.
Skin corrosion/irritation, Category 2	H315	Causes skin irritation.
Skin sensitization, Category 1	H317	May cause an allergic skin reaction.
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336	May cause drowsiness or dizziness.
Specific target organ toxicity — Repeated exposure, Category 1	H372	Causes damage to organs (lungs) through prolonged or repeated exposure.
Aspiration hazard, Category 1	H304	May be fatal if swallowed and enters airways.

Full text of H statements : see section 16

2.2. Label elements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Danger
Hazard statements (GHS US) : H226 - Flammable liquid and vapor
H304 - May be fatal if swallowed and enters airways
H315 - Causes skin irritation

Murdoch’s Hard Sealer

Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Precautionary statements (GHS US)	H317 - May cause an allergic skin reaction
	H336 - May cause drowsiness or dizziness
	H372 - Causes damage to organs (lungs) through prolonged or repeated exposure
	: Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking.
	Keep container tightly closed.
	Ground/Bond container and receiving equipment.
	Use explosion-proof electrical, lighting, ventilating equipment.
	Do not breathe mist, spray, vapors.
	Wash hands, forearms and face thoroughly after handling.
	Do not eat, drink or smoke when using this product.
	Use only outdoors or in a well-ventilated area.
	Contaminated work clothing must not be allowed out of the workplace.
	Wear protective gloves.
	If swallowed: Immediately call a poison center or doctor.
	Do NOT induce vomiting.
	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
	If skin irritation or rash occurs: Get medical advice/attention.
	Wash contaminated clothing before reuse.
	If inhaled: Remove person to fresh air and keep comfortable for breathing.
	Call a poison center or doctor if you feel unwell.
	In case of fire: Use appropriate media to extinguish.
	Store in a well-ventilated place. Keep cool.
	Store locked up.
	Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

2.4. Hazards not otherwise classified

No additional information available

2.5. Unknown acute toxicity

No additional information available

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Distillates (petroleum), hydrotreated light	CAS-No.: 64742-47-8	51.99	STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
(R)-p-mentha-1,8-diene	CAS-No.: 5989-27-5	10.73	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1B, H317 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 3, H412

Murdoch's Hard Sealer

Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Name	Product identifier	%	GHS US classification
Stoddard Solvent	CAS-No.: 8052-41-3	8.091 – 8.422	Flam. Liq. 3, H226 STOT RE 1, H372 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Comments : The concentration ranges are provided due to batch-to-batch variability.

Full text of hazard classes and H-statements : see section 16

SECTION 4 First aid measures

4.1. Description of necessary first-aid measures

First-aid measures general	: First aider: Pay attention to self-protection. Never give anything by mouth to an unconscious person. Give artificial respiration if necessary. Induce artificial respiration with mask fitted with one-way valve or other suitable device but, not mouth-to-mouth. Call a poison center/doctor/physician if you feel unwell.
First-aid measures after inhalation	: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a physician immediately.
First-aid measures after skin contact	: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water . If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Call a physician immediately.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation	: May cause drowsiness or dizziness. Aspiration of the product into the lungs may cause pneumonia.
Symptoms/effects after skin contact	: Causes skin irritation. May cause an allergic skin reaction. Repeated or prolonged skin contact may cause dermatitis and defatting.
Symptoms/effects after eye contact	: May cause eye irritation.
Symptoms/effects after ingestion	: Swallowing the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis.
Chronic symptoms	: Causes damage to organs (lungs) through prolonged or repeated exposure.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment	: If exposed or concerned: Get medical advice/attention. Following inhalation: Subsequent observance for pneumonia and lung edema.
-----------------------------------	--

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Dry chemical powder. Carbon dioxide. Sand/earth. Foam. Water may be ineffective.
Unsuitable extinguishing media	: Do not use a heavy water stream. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam.

5.2. Specific hazards arising from the chemical

Fire hazard	: Flammable liquid and vapor.
Explosion hazard	: May form flammable/explosive vapor-air mixture.
Hazardous decomposition products in case of fire	: Toxic fumes may be released. Carbon dioxide. Carbon monoxide. Unidentified organic and inorganic compounds. Nitrogen oxides. Hydrocarbons.

Murdoch's Hard Sealer

Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

5.3. Special protective equipment and precautions for fire-fighters

- | | | |
|--------------------------------|---|--|
| Firefighting instructions | : | Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection. Large fires: Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Use water spray or fog for cooling exposed containers. Move containers from fire area if it can be done without personal risk. Withdraw immediately in case of rising sound from venting devices or discoloration from tank. ALWAYS stay away from tanks engulfed in fire. For a massive fire, use unmanned hose holders or monitor nozzles, or withdraw from the area and allow fire to burn. Prevent fire-fighting water from entering environment. |
| Protection during firefighting | : | Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing. |

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- | | | |
|------------------|---|---|
| General measures | : | Use only outdoors or in a well-ventilated area. Use non-sparking tools. Use special care to avoid static electric charges. Avoid all personal contact including breathing in the mist, spray, vapors. Avoid contact with eyes, skin and clothing. Do not take actions involving personal risks. Absorb spillage to prevent material-damage. Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. |
|------------------|---|---|

For non-emergency personnel

- | | | |
|----------------------|---|---|
| Protective equipment | : | Wear recommended personal protective equipment. |
| Emergency procedures | : | Evacuate the danger area. If outdoors, move to an area upwind of the danger area. If possible without taking personal risks, remove ignition sources and ventilate area. Prevent other non-emergency personnel from entering the danger area. |

For emergency responders

- | | | |
|---------------------------|---|---|
| Protective equipment | : | Wear recommended personal protective equipment. Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection". |
| Emergency procedures | : | Evacuate unnecessary personnel. Ventilate spillage area. Do not touch or walk on the spilled product. Stop leak if safe to do so. Remove all sources of ignition. |
| Environmental precautions | : | Avoid release to the environment. Do not let the product reach soil, drains, sewers, or surface and ground water. |

6.2. Methods and materials for containment and cleaning up

- | | | |
|-------------------------|---|--|
| For containment | : | Contain with non-combustible inert absorbent. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak, if possible without risk. |
| Methods for cleaning up | : | Take up in non-combustible inert absorbent and place into container for disposal. Contaminated absorbent material may pose the same hazard as the spilled product. Use non-sparking tools. Decontaminate surfaces and equipment with water and detergent. Until a sufficient level of dilution is achieved, the decontamination water may pose the same hazards as the product. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations. Notify authorities if product enters sewers or public waters. |

For further information refer to section 8: "Exposure controls/personal protection", For further information refer to section 13: "Disposal considerations".

Murdoch's Hard Sealer

Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

SECTION 7 Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Ensure good ventilation of the work station. Use only outdoors or in a well-ventilated area. Wear personal protective equipment. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Use explosion-proof equipment. Do not breathe mist, spray, vapors. Avoid contact with eyes, skin and clothing. Flammable vapors may accumulate in the container.
Hygiene measures	: Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.
Additional hazards when processed	: Flammable vapors may accumulate in the container.

7.2. Conditions for safe storage, including incompatibilities

Technical measures	: Proper grounding procedures to avoid static electricity should be followed.
Storage conditions	: Store in a cool, dry and well-ventilated area away from incompatible substances. Protect from sunlight. Avoid extreme temperatures. Keep in fireproof place. Keep container tightly closed. Store locked up.
Incompatible materials for storage	: Strong oxidizing agents. Strong acids.
Heat-ignition	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Packaging materials	: Always store product in container of same material as original container.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

Stoddard Solvent (8052-41-3)	
USA - ACGIH® - Threshold Limit Values	
Local name	Stoddard solvent
ACGIH® TLV® TWA	525 mg/m³
	100 ppm
Remark (ACGIH®)	TLV® Basis: Eye, Kidney & Skin dam; Nausea; CNS impair
Regulatory reference	ACGIH 2026
USA - OSHA - Occupational Exposure Limits	
Local name	Stoddard solvent
OSHA PEL TWA	2900 mg/m³
	500 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
USA - NIOSH - Occupational Exposure Limits	
Local name	Stoddard solvent
NIOSH REL 10h TWA	350 mg/m³
NIOSH REL C	1800 mg/m³ [15-min]
Regulatory reference (US-NIOSH)	OSHA Annotated Table Z-1 (NIOSH Pocket Guide to Chemical Hazards (NPG))

Murdoch's Hard Sealer

Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

8.2. Appropriate engineering controls

Appropriate engineering controls	: Ensure good ventilation of the work station. Use general ventilation, local exhaust ventilation, or process enclosure to keep the airborne concentrations below the permissible exposure limits. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.
Environmental exposure controls	: Avoid release to the environment. Take measures to reduce or limit air emissions and releases to soil and the aquatic environment.

8.3. Individual protection measures, such as personal protective equipment

Personal protective equipment:

Personal protective equipment should be chosen according to national standards and in discussion with the supplier of the protective equipment. Body protection should be chosen depending on activity and possible exposure.

Materials for protective clothing:

Flame retardant antistatic protective clothing

Hand protection:

Wear protective gloves

Eye protection:

Chemical goggles or safety glasses

Skin and body protection:

Wear suitable protective clothing. Body protection should be chosen depending on activity and possible exposure

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Self-contained breathing apparatus

Personal protective equipment symbol(s):



SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Liquid
Color	: Light Amber Clear
Odor	: Mild Citrus
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: 157.2 °C / 315 °F
Flash point	: 45 °C / 113 °F
Flammability (solid, gas)	: Flammable liquid and vapor.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available

Murdoch's Hard Sealer

Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Explosion limits	: No data available
Particle characteristics	: No data available

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10 Stability and reactivity

10.1. Reactivity

Flammable liquid and vapor. May form flammable/explosive vapor-air mixture.

10.2. Chemical stability

Stable under normal conditions of use.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid extreme temperatures. Direct sunlight. Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition. Avoid incompatible materials.

10.5. Incompatible materials

Strong oxidizing agents. Strong acids.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition may produce: Carbon dioxide. Carbon monoxide. Unidentified organic and inorganic compounds. Nitrogen oxides. Hydrocarbons.

SECTION 11 Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

(R)-p-mentha-1,8-diene

LD50 oral rat	> 2000 mg/kg body weight
LD50 dermal rabbit	> 5000 mg/kg body weight

Distillates (petroleum), hydrotreated light

LD50 oral rat	> 5000 mg/kg body weight
LD50 oral	15000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg body weight
LC50 Inhalation - Rat	> 5.28 mg/l air
LC50 Inhalation - Rat (Dust/Mist)	> 5.2 mg/l

Murdoch's Hard Sealer

Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Stoddard Solvent	
LD50 oral rat	> 5000 mg/g
LD50 dermal rabbit	> 3000 mg/kg body weight
LC50 Inhalation - Rat	> 5.5 mg/l air
Skin corrosion/irritation	: Causes skin irritation.
(R)-p-mentha-1,8-diene	
Additional information	Not irritating to rabbits on cutaneous application
Serious eye damage/irritation	: Not classified
(R)-p-mentha-1,8-diene	
Additional information	Not irritating to rabbits on ocular application
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
(R)-p-mentha-1,8-diene	
IARC group	3 - Not classifiable
Reproductive toxicity	: Not classified
(R)-p-mentha-1,8-diene	
NOAEL (animal/female, F0/P)	600 mg/kg body weight
Distillates (petroleum), hydrotreated light	
NOAEL (animal/male, F0/P)	≥ 3000 mg/kg body weight
STOT-single exposure	: May cause drowsiness or dizziness.
Distillates (petroleum), hydrotreated light	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: Causes damage to organs (lungs) through prolonged or repeated exposure.
Distillates (petroleum), hydrotreated light	
NOAEL (oral,rat,90 days)	750 mg/kg body weight
NOAEL (dermal,rat/rabbit,90 days)	≥ 495 mg/kg body weight
Stoddard Solvent	
NOAEL (oral,rat,90 days)	1056 mg/kg body weight
NOAEL (dermal,rat/rabbit,90 days)	2000 mg/kg body weight
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard	: May be fatal if swallowed and enters airways.
Symptoms/effects after inhalation	: May cause drowsiness or dizziness. Aspiration of the product into the lungs may cause pneumonia.
Symptoms/effects after skin contact	: Causes skin irritation. May cause an allergic skin reaction. Repeated or prolonged skin contact may cause dermatitis and defatting.
Symptoms/effects after eye contact	: May cause eye irritation.
Symptoms/effects after ingestion	: Swallowing the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis.

Murdoch's Hard Sealer

Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Chronic symptoms : Causes damage to organs (lungs) through prolonged or repeated exposure.

SECTION 12 Ecological information

12.1. Ecotoxicity

Hazardous to the aquatic environment, short-term (acute) : Very toxic to aquatic life

Hazardous to the aquatic environment, long-term (chronic) : Toxic to aquatic life with long lasting effects

(R)-p-mentha-1,8-diene	
LC50 - Fish [1]	720 µg/l
EC50 - Crustacea [1]	0.307 mg/l
LC50 - Fish [2]	702 µg/l
EC50 - Crustacea [2]	0.51 mg/l
EC50 72h - Algae [1]	0.32 mg/l
EC50 72h - Algae [2]	0.214 mg/l

Distillates (petroleum), hydrotreated light

LC50 - Fish [1]	2.2 mg/l
LC50 - Fish [2]	2200 µg/l

Stoddard Solvent

LC50 - Fish [1]	2.5 mg/l
EC50 96h - Algae [1]	0.58 mg/l
NOEC (chronic)	0.1 mg/l

12.2. Persistence and degradability

Murdoch's Hard Sealer

Persistence and degradability	Not established.
-------------------------------	------------------

(R)-p-mentha-1,8-diene

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

Distillates (petroleum), hydrotreated light

Persistence and degradability	Rapidly degradable
-------------------------------	--------------------

Stoddard Solvent

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

12.3. Bioaccumulative potential

Distillates (petroleum), hydrotreated light

Partition coefficient n-octanol/water (Log Pow)	3.3 – 6
---	---------

12.4. Mobility in soil

No additional information available

Murdoch's Hard Sealer

Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

12.5. Other adverse effects

Ozone : Not classified
Fluorinated greenhouse gases : No

SECTION 13 Disposal considerations

Regional waste regulation : Disposal must be done according to official regulations.
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations : Disposal must be done according to official regulations.
Product/Packaging disposal recommendations : Disposal must be done according to official regulations.
Additional information : Flammable vapors may accumulate in the container. Do not re-use empty containers.
Ecological waste information : The waste of the product should be considered as hazardous as the product itself, with the likelihood of impacting the environment in the same way. Consider the handling and disposal of the waste as defined by the product itself.
List of Hazardous Wastes Codes : U.S. - RCRA (Resource Conservation Recovery Act) - D Waste- Characteristic Waste Codes. D001: IGNITABLE WASTE.

SECTION 14 Transport information

In accordance with DOT / IMDG / IATA

DOT	IMDG	IATA
14.1. UN number		
UN1263	1263	1263
14.2. Proper Shipping Name		
Paint related material	PAINT RELATED MATERIAL	Paint related material
14.3. Transport hazard class(es)		
3	3	3
14.4. Packing group		
III	III	III
14.5. Environmental hazards		
	Dangerous for the environment: Yes Marine pollutant: Yes	
No supplementary information available		

14.6. Transport in bulk

Not applicable

14.7. Special precautions for user

DOT

UN-No. (DOT) : UN1263
DOT Packaging Exceptions (49 CFR 173.xxx) : 150
DOT Packaging Non Bulk (49 CFR 173.xxx) : 173
DOT Packaging Bulk (49 CFR 173.xxx) : 242
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 60 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 220 L

Murdoch's Hard Sealer

Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

IMDG

Special provision (IMDG) : 163, 223, 367, 955
Limited quantities (IMDG) : 5 L
Excepted quantities (IMDG) : E1
Packing instructions (IMDG) : P001, LP01
Packing provisions (IMDG) : PP1
IBC packing instructions (IMDG) : IBC03
Tank instructions (IMDG) : T2
Tank special provisions (IMDG) : TP1, TP29
EmS-No. (Fire) : F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS
EmS-No. (Spillage) : S-E - SPILLAGE SCHEDULE Echo - FLAMMABLE LIQUIDS, FLOATING ON WATER
Stowage category (IMDG) : A
Properties and observations (IMDG) : Miscibility with water depends upon the composition.

IATA

PCA Excepted quantities (IATA) : E1
PCA Limited quantities (IATA) : Y344
PCA limited quantity max net quantity (IATA) : 10L
PCA packing instructions (IATA) : 355
PCA max net quantity (IATA) : 60L
CAO packing instructions (IATA) : 366
CAO max net quantity (IATA) : 220L
ERG code (IATA) : 3L

SECTION 15 Regulatory information

15.1. Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, except for:		
Urethane Polymer	CAS-No.	8.085 – 8.415%

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

CANADA

(R)-p-mentha-1,8-diene (5989-27-5)

Listed on the Canadian DSL (Domestic Substances List)

Distillates (petroleum), hydrotreated light (64742-47-8)

Listed on the Canadian DSL (Domestic Substances List)

Stoddard Solvent (8052-41-3)

Listed on the Canadian DSL (Domestic Substances List)

Murdoch’s Hard Sealer

Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

EU-Regulations

No additional information available

National regulations

(R)-p-mentha-1,8-diene (5989-27-5)
Listed on INSQ (Mexican National Inventory of Chemical Substances)

Distillates (petroleum), hydrotreated light (64742-47-8)
Listed on INSQ (Mexican National Inventory of Chemical Substances)

Stoddard Solvent (8052-41-3)
Listed on INSQ (Mexican National Inventory of Chemical Substances)

15.3. State regulations

 **WARNING:**

This product can expose you to chemicals including Benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Component	State or local regulations
Stoddard Solvent(8052-41-3)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - New York City - Right to Know Hazardous Substances List; U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16 Other information

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Issue date : 9/8/2026

Full text of hazard classes and H-statements	
H226	Flammable liquid and vapor
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H336	May cause drowsiness or dizziness
H372	Causes damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.